



355 - 365 Wp 120 MONOCRYSTALLINE HALF-CUT CELLS

AEG solar modules combine the most advanced technology with high reliability in manufacture to offer you a product meant for high achievements.



OPTIMIZED DESIGN MAXIMUM EFFICIENCY

AEG solar modules with half-cut cells (M6) and 9 busbar technology are designed to maximize efficiency and plant performance. The 120 cm extra-long cables allow more installation flexibility and comfort.



FULL BLACK, PREMIUM LOOK

The careful selection of components (cells, backsheet and frames) ensures a premium product look and provides extra aesthetical value.

COMPREHENSIVELY CERTIFIED

AEG solar modules and production facilities are compliant with the the latest standards to guarantee safety and reliability. Production facilities are certified according to ISO 9001, ISO 14001 and OHSAS 18001. AEG solar products are certified among others by:



YOUR ADVANTAGE AT A GLANCE

Premium solar panel with quality components
High efficiency - up to 365 Wp
Product certified IEC 61215:2016, IEC 61730:2016
15 years Product warranty
25 years linear Power warranty



PHOTOVOLTAIC MODULE AS-M1203B-H (M6 cells)

AEG

ELECTRICAL CHARACTERISTICS AT STC¹

		AS-M1203B-H-355	AS-M1203B-H-360	AS-M1203B-H-365
Nominal Power (P _{max})	[Wp]	355	360	365
Power Sorting ²	[Wp]	-0 / +5	-0 / +5	-0 / +5
Maximum Power Voltage (V _{mp})	[V]	33.24	33.49	33.73
Maximum Power Current (I _{mp})	[A]	10.68	10.75	10.82
Open Circuit Voltage (V _{oc})	[V]	39.80	40.14	40.41
Short Circuit Current (I _{sc})	[A]	11.15	11.21	11.29
Module Efficiency (η _m)		19.2%	19.5%	19.7%
Maximum System Voltage	[V]	1000	1000	1000
Series Fuse Maximum Rating	[A]	20	20	20


ELECTRICAL CHARACTERISTICS NMOT³

Maximum Power (P _{max})	[W]	264.7	268.5	272.2
Maximum Power Voltage (V _{mp})	[V]	30.99	31.22	31.45
Maximum Power Current (I _{mp})	[A]	8.54	8.60	8.65
Open Circuit Voltage (V _{oc})	[V]	37.42	37.74	37.99
Short Circuit Current (I _{sc})	[A]	8.97	9.02	9.08

MECHANICAL CHARACTERISTICS

Solar cells	120 [(6 x 10) x 2] monocrystalline silicon, 166x 83 mm (M6) half-cut cells
Front glass	3.2 mm (0.12") high-transparency glass
Backsheet	Black backsheet
Encapsulant	EVA (Ethylene-Vinyl Acetate)
Frame	Anodized aluminum alloy, black color
Junction box	IP68, 3 bypass diodes
Cables	UV resistant cable 120 cm (47.2"), sec.4.0 mm ²
Connectors	MC4 compatible connectors
Dimensions	1765 mm x 1048 mm x 35 mm (69.48" x 41.2" x 1.37")
Weight	20 kg (44.09 lbs)
Maximum load	Wind: 2400 Pa / Snow: 5400 Pa

TECHNICAL DRAWINGS



Module dimensions in the technical picture are expressed in mm with tolerance +2 mm (+0.079")

1- Standard Test Conditions (STC): Irradiance 1000 W/m²; Air Mass AM = 1.5; Cell Temperature 25°C; Tolerance on P_{max} ± 3%; Tolerance on V_{oc} ± 3%; Tolerance on I_{sc} ± 5%

2- AEG photovoltaic modules are classified according to a principle of positive power tolerance: the Power Output measured at STC of the delivered modules exceeds their assigned Nameplate Nominal Power at STC within a power tolerance range between -0 Wp and +5 Wp.

3- Nominal Module Operating Temperature (NMOT): Irradiance 800 W/m²; Wind Speed 1m/s; Ambient Temperature 20°C; Air Mass AM=1.5

4- No less than 98% of the minimum "Peak Power at STC" in the first year; power output decline no more than 0.55% per year thereafter). Full text of the Warranty Terms available at: www.aeg-industrialsolar.de

© Solar Solutions GmbH. Specifications in this datasheet are subject to change without notice. Code: AS-M1203B-H-M6-KM0N1-9BB-355-365 / version 2020/08/V1EN

AEG is a registered trademark used under license from AB Electrolux (publ).

TEMPERATURE CHARACTERISTICS

NOCT	44°C ± 2°C
P _{max} Temp. Coefficient (γ)	-0.34 %/C
V _{oc} Temp. Coefficient (β)	-0.27 %/C
I _{sc} Temp. Coefficient (α)	0.04 %/C
Operating temperature	-40°C to + 85°C

PACKING CONFIGURATION


Packing configuration	31 pcs / pallet
Loading capacity	806 pcs / 40 ft container

WARRANTIES

Product warranty	15 years
Performance warranty	25 years, linear ⁴

I-V CURVES / IRRADIANCES

Test temperature: 25 °C



CONTACT US

SOLSOL s.r.o. | Králova 298/4 | Brno 616 00 | Czech Republic

Tel: +42 0 773 576 737 | Mail: sales@solsol.cz

www.solsol.cz